

Straight Blade Devices 15A, 125V, 2 Pole, 3 Wire Grounding Valise Plug

HUBBELL



Features

- Hinged one piece body design for easy assembly
- Powerful, offsetting cord grips clamp on individual conductors
- Assembly screws are captive and will not fall out while wiring
- Insulation displacement terminals reduce assembly time

Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Insulation displacement terminals, black nylon	.230"-.360"(5.8-9.1)	783585013428	HBL5966VBLK

Listings

UL Listed to UL498 File E1706
CSA Certified to C22.2 No. 42 File 280
NEMA® WD-6 Compliant

Specifications

Housing	Nylon
Blades	Brass
Assembly Screws	Plated Steel

Performance

Electrical


Current Interrupting Certified for current interrupting at full rated current
Dielectric Voltage Withstands 2,000V minimum

Mechanical


Product Identification Ratings are a permanent part of the device
Terminal Accommodation #18-16 AWG. Stranded copper wire only.
Terminal Identification Terminals identified in accordance with UL 498 and CSA

Environmental

Flammability UL 94 HB or better
IP Suitability IP20
Operating Temperatures Maximum continuous 75°C; minimum -40°C (w/o impact)



CORD CLAMPS ACCOMMODATE THE FOLLOWING:
5966-VBLK - .230 - .360 DIA. INSULATION
5967-VBLK - .360 - .575 DIA. INSULATION



Resources

Customer Use Drawing
eCatalog

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

