

Artikeldatenblatt

Cisco power cable CAB-AC-20A-SG-C20

PART NO: CAB-AC-20A-SG-C20

Power cable for Cisco Nexus 7700 N77-HV-3.5KW power supply and other equipment.

Length: 2 Meters (6.5 ft.)



ELECTRICAL SPECIFICATIONS

VOLTAGE (AC/DC)	UL 1977 / CSA 22.2	600
	IEC	400
CURRENT RATING (AMPERES)		40
DIELECTRIC WITHSTANDING VOLTAGE		3300
OPERATING TEMPERATURE		-20° to 80°C / -4° to 176°F

MATERIALS (RoHS COMPLIANT)

HOUSING:	Polycarbonate UL94 V-0 Halogen Free
CONTACTS:	Copper, Silver Plate
CABLE / STRAIN RELIEF:	Thermoplastic UL94 V-2
CABLE ASSEMBLY:	14 AWG SJT UL 250V 105C

MECHANICAL SPECIFICATIONS

CONTACT RETENTION:	89 N / 20 lbf
PLUG LATCH RETENTION:	89 N / 20 lbf
PANEL LATCH RETENTION:	267 N / 60 lbf
DURABILITY:	5000 cycles - no load



SPAWA Handelsagentur Inh. Jörg Hosang
Groß- und Einzelhandel von Spannungswandler und US Elektromaterial
Techritzer Str.7
02692 Doberschau
Germany
Tel.: 0049-3591-203525
Fax.:0049-3591-203782
info@spawa.de
www.spawa.de / www.spannungswandler.us
Umsatzsteuer-Identifikationsnummer gemaess Paragraph 27a
Umsatzsteuergesetz:DE 812933281